

EuroPur Parquet Adhesive

See instructions for application and curing times for details.

Features

See instructions for application and curing times for details. **Waterproof** and **flexible** adhesive for all wood species.

Application Area

Parquet, parquet tiles, wood and stone tiles.

Application Procedure

See instructions for the correct use of adhesive. **Apply adhesive to the substrate** and **press the tile into the adhesive**. **Remove excess adhesive** with a **scraper**. **Wipe off the excess adhesive** with a **damp cloth**. **Do not walk on the adhesive** until it is **fully cured**. **Do not use water** to clean the adhesive. **Do not use oil-based products** to clean the adhesive. **Do not use solvents** to clean the adhesive.

Composition

It is a 2-component adhesive (epoxy resin).

Storage

It should be stored in a cool, dry place.

Notes

Always use the adhesive in the correct ratio. **Do not use water** to clean the adhesive. **Do not use oil-based products** to clean the adhesive. **Do not use solvents** to clean the adhesive.

Technical Properties

PROPERTY	VALUE
Modulus	1.2 GPa
Strength	20 MPa
Adhesion	10 MPa
Flow	10 MPa
Shrinkage	0.1% (20°C/24h)
WV	0.01

WV: Water vapor transmission coefficient, g/m²/day at 30°C and 65% RH.

Shrinkage: Shrinkage of the adhesive after curing at 20°C for 24 hours.

Packaging

10 kg/22 lb (4)