DuroPur Rubber Floor Adhesive

It is a solvent-free two component polyurethane based rubber and sports floor adhesive.

Properties

- Has resistance against humidity and water
- Has thixothropic properties.
- Solvent -free and odorless.
- Has good adhesion properties to many substrates.
- Provides permanent adhesion to concrete, cementicious systems, timber.

Application Areas

- Shockpads and Rubber Tiles

Application Instructions

The resin component should be thoroughly stirred to incorporate any slight separation, whilst continuing stirring the contents of the hardener container should be added, Continue stirring until a homogeneous mix is obtained. The mixed material must be used within 30-40 minutes of mixing at 20°C The surface must be dry and clean. On uneven or rough surfaces, use DuroPur PU concrete primer before applying adhesive. On even but claimy, dusty and unprepared surfaces, prime the surface with a proper primer from DuroPur primer portfolio.

PACKAGING TYPE

- 9kg +1kg Plastic Pail(A+B)

Technical Properties

PROPERTIES	VALUES
Colour	Krem
Mixing Ratio	9 : 1 (Ağırlıkça)
Pot-life (23°C)	(23°C) 30-40 dk.
Application temperature	Min 5°C
Curing	(20°C ve %60 bağıl nem) : 4 saat
Consumption	m² başına 1 kg kullanılır (yüzey emiciliğine bağlıdır)
Storage	12 months under room conditions

NOTE: Substrate must be dry, clean, free from dust, grease and oil. Application must be done between 5°C and 30 °C.