

EuroPur Top Coat 1K

NOTE: Before painting, ensure that the surface is clean, free from contaminants, and free from the risk of moisture condensation.

APPLICATION INSTRUCTIONS

- Apply the product with a roller or brush to the substrate to be treated, ensuring a uniform layer of 200-250 g/m².
- Allow the product to dry for 24 hours.
- For a second coat, wait 24 hours before applying.
- For a third coat, wait 48 hours before applying.
- For a fourth coat, wait 72 hours before applying.

ADVANTAGES

- High resistance to abrasion and impact.
- Excellent adhesion.
- Easy to apply.
- High resistance to UV radiation.
- High resistance to chemical products.
- High resistance to salt crystallization.
- High resistance to acid rain.
- High resistance to water.
- High resistance to pollution.

PRODUCT INFORMATION

Composition

- Epoxy
- Polyurethane

Colors

- White
- Grey
- Black
- RAL 7035 (RAL color chart)

Weight

- The net weight of the product is given in grams per liter and is subject to change without notice.

Storage and Shelf Life

- Store in a cool, dry place (5°C to 25°C).
- Shelf life: 12 months from the date of manufacture.

Preparation

1. Mix the two components.

2. Stir the mixture for 5 minutes to ensure a uniform mixture.

Application and Drying

For application, use a roller or brush. Ensure the surface is clean, free from contaminants, and free from the risk of moisture condensation. Allow the product to dry for 24 hours before applying a second coat.

Preparation of Surface

Ensure the surface is clean, free from contaminants, and free from the risk of moisture condensation.

Application

Apply the product with a roller or brush to the substrate to be treated.

Ensure a uniform layer of 200-250 g/m².

- Allow the product to dry for 24 hours before applying a second coat.
- For a third coat, wait 48 hours before applying.
- For a fourth coat, wait 72 hours before applying.
- For a fifth coat, wait 96 hours before applying.

TECHNICAL DATA

PROPERTY	UNIT	VALUE	TEST METHOD
Viscosity (25°C)	Pa·s	100-150	ISO 3219
Density	kg/m ³	1200	ISO 1181
Flash Point (Cup)	°C	25	ISO 2702
Flash Point (COC)	°C	25	ISO 2702
Flash Point (COC)	°C	25	ISO 2702
Flash Point (COC)	°C	25	ISO 2702
Flash Point (COC)	°C	25	ISO 2702
Flash Point (COC)	°C	25	ISO 2702
Flash Point (COC)	°C	25	ISO 2702
Flash Point (COC)	°C	25	ISO 2702
Flash Point (COC)	°C	25	ISO 2702
Flash Point (COC)	°C	25	ISO 2702
Flash Point (COC)	°C	25	ISO 2702